

STINGRAY®

- Flow efficient 3" waterway allows for flows up to 1250 gpm
- All construction features designed to minimize maintenance needs
 - Choice of corrosion resistant brass or lightweight Elk-O-Lite® construction
 - Fully enclosed gearcase with stainless steel worm
 - Bronze balls in all swivel joints
 - Grease zerks for easy lubrication
- Flexible installation options include numerous base options and a hydrant mounting choice
- Compact size — 16" high or 21" high — is extremely versatile, allowing the monitor to serve a variety of real-world needs
- Built-in shut-off capabilities (with the Stingray® IV) from a full flow 3" ball valve

Stingray® Selector Guide

INLET SIZES / TYPES			OUTLET SIZE	VERTICAL TRAVEL		INTEGRAL COMPONENTS		MATERIALS		CERTIFICATIONS		DIMENSIONS				ILLUSTRATION	MODEL
NPT	150 # ANSI Flange		2.5"	-60° to +70°	-60° to +90°	Ball Valve	Pressure Gauge	Brass	Elk-O-Lite®	CE	FM Approved	Width (in.)	Depth (in.)	Height (in.)	Weight (Lbs.)		
3"	3"	4"	NHT	(130°)	(150°)	3"											
o	o	s	•	o	s	s		•		•	•	14.75	15.75	20.375	68.25	1	8393IV
o	o	s	•	s	o		o	•		•	•	14.75	15.75	15.75	47.5	2	8393
o	o	s	•	s	o		o	•		•	•	14.75	15.75	15.75	16.0	2	8393-A
						4	3										Illustration

KEY s = standard o = option

Components & Options Chart

COMPONENTS & OPTIONS	ILLUSTRATION	MODEL
Companion Flange Kits	3" 150# ANSI steel flange with bolts and gaskets	81315001
	4" 150# ANSI steel flange with bolts and gaskets	81317001