

Portable Carts

- Portable wheeled carts come furnished with a flow-efficient, built-in 4" manifold
- Wheels feature pneumatic tires and wheel locks
- The monitors have stop positions at 45° on either side of center and 20° above horizontal
- Cart specific highlights include:
 - The two wheel cart attaches with a 17/8" or 2" coupler; to the vehicle for extra stability during flow; two hose beds each capable of holding two (2) 50' sections of 21/2" or 3" hose
 - The four wheel cart has a detachable "tee" handle, optional hose racks above the wheels — each capable of holding a 50' "donut roll" of 21/2" hose
- Liquid-filled pressure gauge

Portable Cart Selector Guide

Cart Type/ GPM (LPM)	Monitor	INLET OPTIONS				OUT-LET	CART FEATURES				VERTICAL TRAVEL	CONTROLS	DIMENSIONS (Inches)			Weight (Lbs.)	ILLUSTRATION	MODEL
		2 x 2.5" NHT*	2 x 2.5" NHT* +4" Storz	2 x 2.5" NHT* +5" Storz	4 x 2.5" NHT*	2.5" NHT	T Handle	Coupler	Pressure Gauge	Hose Beds	+20° to 70° (50°)	Single Hand-wheel	Width	Depth	Height			
2-Wheel/ 1000 (3875)	Stingray 8393	s	o	o	o	•		⊕	s	s	•	s	67.00	72.00	34.00	310.0	1	8393TW
4-Wheel/ 750 (2839)	Stingray 8393	s	o	o	o	•	s		s	o	•	s	67.00	72.00	34.00	230.0	2	8393FW

KEY s = standard o = option

* Clappered female swivel inlets.

** This feature will change the height of the end product.

⊕ Storz inlet carts have 2.0" coupler - 2 x 2.5" & 4 x 2.5"NHT have 1.875" coupler