

























Master Stream Selector Guide

Designed for use in fixed system applications. Adjustable nozzles can be pre-set at the factory or set in the field at time of installation. The fog pattern, which can be set up to 120°, can easily be set or adjusted at the job site.

		AVAILABLE BASE	PRODUCT	DESCRIPTION	MATERIAL			"QUICK-KEY"
FIXED	5000E	1.5		<ul style="list-style-type: none"> Combination nozzle 12 or 24 VDC enclosed and sealed motor 	Brass	Composite	Elk-O-Lite®	 
		2.5						
3.5								
		Available GPM (LPM)						
		15-475 (57-1798)						
AUTOMATIC	SM-10FE	1.5		<ul style="list-style-type: none"> Simplifies fireground hydraulics Maintains effective flow stream 12 or 24 VDC enclosed and sealed motor 	Brass	Composite	Elk-O-Lite®	 
		2.5						
3.5								
		Available GPM (LPM)						
		20-120 (76-454)						
FIXED/SELECTABLE	R.A.N.	1.5		<ul style="list-style-type: none"> Designed for use with R.A.M. Integral stream shaper 1/4 turn stream adjustment Optional oscillating configuration available 	Brass	Composite	Elk-O-Lite®	  
		2.5						
3.5								
		Available GPM (LPM)						
		250-500 (946-1893)						
AUTOMATIC	X-STREAM®	1.5		<ul style="list-style-type: none"> Simplifies fireground hydraulics Maintains effective flow stream Calibrated at lower pressures - 75 & 80 PSI 	Brass	Composite	Elk-O-Lite®	      
		2.5						
3.5								
		Available GPM (LPM)						
		300-2000 (1136-7571)						
SELECTABLE	6000	1.5		<ul style="list-style-type: none"> Designed for use with Sidewinder EXM Maintains effective flow stream Motor enclosed and sealed 	Brass	Composite	Elk-O-Lite®	 
		2.5						
3.5								
		Available GPM (LPM)						
		15-700 (60-2700)						
FOAM EXPANSION TUBES		1.5		<ul style="list-style-type: none"> Quick-snap connection Composite or metal construction 	Brass	Composite	Elk-O-Lite®	 
		2.5						
3.5								
		Available GPM (LPM)						